

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Gatorback Coating

HMS CODES: H F R P

PRODUCT CODE(S): GB02, GB03

2 4 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: R&M Car Care, Inc.

ADDRESS: 4401 River Close Blvd.

DATE PRINTED: 10/24/2005

Valrico, FL 33594

NAME OF PREPARER: KL

EMERGENCY PHONE: Chemtrec 800-424-9300

INFORMATION PHONE: 813-294-9223

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	OCCUPATIONAL EXPOSURE LIMITS				VAPOR PRESSURE		WEIGHT %
	CAS NUMBER	OSHA	ACGIH TLV	OTHER1	mm HG @	TEMP (F)	
*Xylene	1330-20-7	100 ppm	100 ppm	N/A	36.7	86	10-20
*Toluene	108-88-3	200 ppm	200 ppm	100 ppm	36.7	86	10-20
Aromatic Hydrocarbon	64742-95-6	mixture	mixture	N/A	12.5	77	10-20
PM Acetate	10-65-9	200 ppm	200 ppm	N/A			1-10
ARomatic Hydrocarbon	336-454-1161	mixture	mixture	N/A			10-20
Acrylic Resin	Proprietary						10-15

* Indicates toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372

WARNING: DETECTABLE AMOUNTS OF A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM **MAY** BE PRESENT IN THIS PRODUCT

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING RANGE	<140 C	SPECIFIC GRAVITY (H2O=1):	0.924
VAPOR DENSITY:	Heavier than air		
EVAPORATION RATE:	Faster than n-Butyl Acetate		
COATING V.O.C.:	6.3	MATERIAL V.O.C.	6.3
SOLUBILITY IN WATER:	Stable		
APPEARANCE AND ODOR:	Opaque, medium viscosity, pourable liquid		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >40 F
FLAMMABILITY LIMITS - LOWER N/A UPPER: N/A
EXTINGUISHING MEDIA: Fight source of fire. Dry chemical, carbon dioxide, chemical foam.

SPECIAL FIRE FIGHTING PROCEDURES:

Water spray to cool containers. If this material is involved in a fire. NIOSH approved self-contained breathing apparatus should be worn

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors are heavy, may concentrate at lower levels creating hazard. At high temperatures, containers may burst.

SECTION V - REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID: Excessive heat and freezing temperatures.

INCOMPATIBILITY (MATERIALS TO AVOID):

Oxidizing agents, alkalis and high temperatures.

SECTION V - REACTIVITY DATA (continued)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Chlorine, hydrogen chloride (Hydrochloric acid), phosgene.

HAZARDOUS POLYMERIZATION:

Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and asphyxiation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Moderate irritation, redness, blurred vision.

SKIN ABSORPTION RISKS AND SYMPTOMS OF EXPOSURE:

Moderate irritation, redness, dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Gastrointestinal irritation, vomiting, diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Acute: Continuous skin contact may cause dermatitis. May result in irritation of the skin, eyes and respiratory tract. Chronic: Not determined.

CARCINOGENICITY: NTP?: No IARC?: No OSHA?: Yes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Bronchitis, CNS disorders, allergies, nausea

EMERGENCY FIRST AID PROCEDURES:

Inhalation: If vapors are bothersome, remove to fresh air. Skin Contact: Avoid prolonged contact. Wash with large amounts of water. If irritation persists, see physician. Eye contact: Flush with large amounts of water until all material is removed. If irritation persists, see physician.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Confine as much as possible. Dike and absorb with inert material such as vermiculite. Transfer to containers for disposal.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE (continued)

WASTE DISPOSAL METHOD:

Dispose of in accordance with all Federal, State, and local ordinances.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Wear gloves, goggles and protective clothing to prevent contact with product. Store material at temperatures between 36F (2C) and 120F (49C). Do not store containers in direct sunlight.

OTHER PRECAUTIONS:

Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid spontaneous combustion of contaminated rags or other ignitable material. Keep out of reach of children.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION:

None required if adequate ventilation is provided.

VENTILATION:

Adequate to keep exposure limits below those listed in SECTION II

PROTECTIVE GLOVES:

Impervious rubber gloves.

EYE PROTECTION:

Chemical splash goggles (ANSI Z 87.1 or approved equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear protective clothing to prevent contact with products.

WORK / HYGENIC PRACTICES:

Wash hands before eating, smoking or using the bathroom.

SECTION IX - TRANSPORTATION AND SHIPPING

DOT/UN SHIPPING NAME:	Paint	FREIGHT DESCRIPTION
DOT/UN CLASS:	3	Paint
NA/UN NUMBER:	UN1263	
PACKING GROUP:	II	
DOT LABELS REQUIRED	Flammable Liquid	

SECTION IX - DISCLAIMER

R & M Car Care, Inc. urges each customer or recipient of this MSDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this MSDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Since conditions for the use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product.